

Harry Porrins,
Sales & Marketing Manager,
Advanced Concrete Technologies,
Cnr Cook & Bannister Roads,
Canning Vale. WA. 6155.

10/12/2007

Dear Harry,

RE: Render coatings for ecobrick.

Thank you for the opportunity to provide a recommendation for the use of Rockcote products with the ecobrick.

We have sent the samples provided to our Queensland laboratory for checking and they have determined that the ecobrick will accept Rockcote products under the following general procedures.

First stage - surface preparation

The surface of the ecobricks should be patched with an appropriate cement based filler to ensure is that any indentations are removed. The surface will then require treatment with Rockcote Acrybond sealer.

Second stage

The application of Rockcote PM100 render at a consistency between 4 to 6mm in depth.

Third stage

The application of the chosen finish coat at the recommended rate.

The surface coats can be a Paint finish, Sandcote or Textured finish in a number of colours. Samples and technical information will be supplied on request plus our application contractors are industry experienced and trained in the correct use of our products.

The Rockcote business philosophy is built around environmentally sustainable products and practices and we ensure that these practices are carried out on all projects.

Our team in WA is available to assist you and your clients in both the technical and practical application of Rockcote products.

Yours sincerely,



Paul Clarke

Managing Director - Rockcote WA

Australia's Foremost
Manufacturer of
Architectural Coatings

Rockcote WA
ABN 71 122 715 057

Unit 4
13 Inverness Street
Malaga WA 6090

Tel: (08) 9248 4496
Fax: (08) 9248 4497

sales@rockcotewa.com.au

www.rockcotewa.com.au

